## \*TM 5-818-5/AFM 88-5, Chap 6/NAVFAC P-418

TECHNICAL MANUAL NO. 5-818-5 AIR FORCE MANUAL NO. 88-5, Chapter 6 NAVY MANUAL NO. P-418

HEADQUARTERS
DEPARTMENT OF THE ARMY,
THE AIR FORCE,
AND THE NAVY

WASHINGTON, DC 15 November 1983

## **DEWATERING AND GROUNDWATER CONTROL**

			Paragraph	Page
CHAPTER	1.	INTRODUCTION	1 Gragrapis	1 Wgc
	-	Purpose and scope	1-1	1-1
		General	1-2	1-1
		Construction dewatering	1-3	1-1
		Permanent groundwater control	1-4	1-2
	2.	METHODS FOR DEWATERING, PRESSURE RELIEF, AND SEEPAGE CUTOFF		
		General	2-1	2-1
		Types and source of seepage	2-2	2-1
		Sumps and ditches	2-3	2-1
		Wellpoint systems	2-4	2-2
		Deep-well systems	2-5	2-4
		Vertical sand drains	2-6	2-5
		Electro-osmosis	2-7	2-5
		Cutoffs	2-8	2-5
		Summary of groundwater control methods	2-9	2-8
		Selection of dewatering system	2-10	2-8
	3.	GEOLOGIC, SOIL, AND GROUNDWATER INVESTI- GATIONS		
		General	3-1	3-1
		Geologic and soil conditions	3-2	3-1
		Groundwater characteristics	3-3	3-4
		Permeability of pervious strata	3-4	3-4
		Power	3-5	3-8
		Surface water	3-6	3-8
	. 4.	DESIGN OF DEWATERING, PRESSURE RELIEF, AND GROUNDWATER CONTROL SYSTEMS		
		Analysis of groundwater flow	4-1	4-1
		Mathematical and model analyses	4-2	4-1
		Flow-net analyses	4-3	4-29
		Electrical analogy seepage models	4-4	4-29
		Numerical analyses	4-5	4-34
		Wellpoints, wells, and filters	4-6	4-34
		Pumps, headers, and discharge pipes	4-7	4-36
		Factors of safety	4-8	4-40
		Dewatering open excavations	4-9	4-42
		Dewatering shafts and tunnels	4-10	4-47
		Permanent pressure relief systems	4-11	4-48
		Freezing	4-12	4-48
		Control of surface water	4-13	4-49
	5.	INSTALLATION OF DEWATERING AND GROUND-WATER CONTROL SYSTEMS		
		General	5-1	5-1
		Deep-well systems	5-2	5-1
		Wellpoint systems	5-3	5-2
		Vertical sand drains	5-4	5-5
		Cutoffs	5-5	5-5
	6	PiezometersOPERATION AND PERFORMANCE CONTROL	5-6	5-6
	-	General	6-1	6-1
		Operation	6-2	6-1
	7.	Control and evaluation of performance	6-3	6-2
	٠.	General	7-1	7-1

<sup>\*</sup>This manual supersedes TM 5-818-5/AFM 88-5, Chap 6/NAVFAC P-418, April 1971.

## TM 5-815-5/AFM 88-5, Chap 6/NAVFACP-418

	Paragraph	Page
	Types of specifications	7–1
	Data to be included in specifications	7–2
	Dewatering requirements and specifications 7–4	7–2
	Measurement and payment	7–3
•	Examples of dewatering specifications 7–6	7–3
APPENDIX	A. REFERENCES AND BIBLIOGRAPHY	A-1
	B. NOTATIONS	B-1
	C. FIELD PUMPING TESTS	C-1
	D. EXAMPLES OF DESIGN OF DEWATERING AND PRES- SURE RELIEF SYSTEMS	D-1
	E. TRANSFORMATION OF ANISOTROPIC SOIL CONDITIONS TO ISOTROPIC SOIL CONDITIONS	E-1
	F. WELL AND TOTAL DISCHARGE MEASUREMENTS	F-1
	G. EXAMPLES OF DETAILED DEWATERING SPECIFICA-	
	TIONS	G-1
Figure	LIST OF FIGURES	Page
1-1	Installation of piezometers for determining water table and arte-	1 aye
1-1	<u> </u>	1.0
	sian hydrostatic pressure	1–2
1–2	Permanent groundwater control system	1–3
2–1	Dewatering open excavation by ditch and sump	2–2
2–2	Self-jetting wellpoint	2–3
2–3	Use of wellpoints where submergence is small	2-4
2–4	Drainage of an open deep cut by means of a multistage wellpoint system	2–4
9.5		
2–5	Vacuum wellpoint system	2-5
2–6	Jet-eductor wellpoint system for dewatering a shaft	2–6
2–7	Deep-well system for dewatering an excavation in sand	2–7
2–8	Deep wells with auxiliary vacuum system for dewatering a shaft	
	in stratified materials	2–8
2–9	Sand drains for dewatering a slope	2–9
2–10	Electro-osmotic wellpoint system for stabilizing an excavation	0.0
	slope	2–9
2–11	Grout curtain or cutoff trench around an excavation	2–10
2–12 2–13	Dewatering systems applicable to different soils	2–13
	result of dewatering operations	2-14
3–1	Geologic profile developed from geophysical explorations	3–2
3-2	Permeameters: (a) constant head and (b) falling head	3–3
3–3	Specific yield of water-bearing sands versus D <sub>10</sub> , South Coastal Basin, California	3-4
3–4	$D_{10}$ versus in situ coefficient of permeability—Mississippi River	
3–5	Valley and Arkansas River ValleyFormulas for determining permeability from field falling head	3–6
- J	tests	3–7
3–6	Inches of rainfall during 10- and 30-minute and 1-hour periods	3–8
4-1	Flow and head for fully penetrating line slot; single-line source;	
	artesian, gravity, and combined Flows	4–2
4-2	Height of free discharge surface h <sub>s</sub> ; gravity flow	4–3
4–3	Flow and head for partially penetrating line slot; single-line	4 4
	source; artesian, gravity, and combined flows	4–4
4–4	Flow and head for fully and partially penetrating line slot; two-	4.5
4 -	line source; artesian and gravity flows	4–5
4–5	Flow and head (midway) for two partially penetrating slots; two-	4.0
	line source; artesian and gravity flows	4–6
4–6	Flow and head for fully and partially penetrating circular slots; circular source; artesian flow	4–7
4–7	Head at center of fully and partially penetrating circular slots; cir-	-1-1
4-1	aular courses or tories flow	4.0
4.0	cular source; artesian flow	4–8
4–8	Flow and drawdown at slot for fully and partially penetrating rec-	
	tangular slots; circular source; artesian flow	4–9
4–9	Head within a partially penetrating rectangular slot; circular	
	source; artesian flow	4–10
4–10	Flow and drawdown for fully and partially penetrating single	
	wells; circular source; artesian flow	4–11

## TM 5-815-5/AFM 88-5, Chap 6/NAVFACP-418

Figure		Page
4-11	Flow and <b>drawdown</b> for fully and partially penetrating single wells; circular source; gravity flow	4-12
4-12	Flow and drawdown for fully penetrating single well; circular source; combined artesian and gravity flows	4-13